

Multi Panel (Multi Panel)

Selector: CRS	
Display Value	Display NAV OBS:1
Clockwise turn	Increment NAV OBS:1 by 1
Counterclockwise turn	Decrement NAV OBS:1 by 1

Flaps UP	
Activate (short)	Send FLAPS_DECR-Event (Parameter: 0)
Activate (long)	Send FLAPS_UP-Event (Parameter: 0)

Flaps DOWN	
Activate (short)	Send FLAPS_INCR-Event (Parameter: 0)
Activate (long)	Send FLAPS_DOWN-Event (Parameter: 0)

Power configuration	
Actions that can control the device's virtual power	
[SIMCONNECT:AVIONICS MASTER SWITCH] == 1	Send command Device: Virtual Power ON to Multi Panel
[SIMCONNECT:AVIONICS MASTER SWITCH] == 0	Send command Device: Virtual Power OFF to Multi Panel

Pitch trim	
Nose UP	Send ELEV_TRIM_UP-Event (Parameter: 0)
Nose DOWN	Send ELEV_TRIM_DN-Event (Parameter: 0)

Selector: HDG	
Display Value	
[LVAR:A320_FCU_SHOW_SELECTED_HEADING] == 1	Display A32NX_AUTOPILOT_HEADING_SELECTED (LVAR)
[LVAR:A32NX_AUTOPILOT_HEADING_SELECTED] == -1	Display AUTOPILOT HEADING LOCK DIR:2
Clockwise turn	Send HEADING_BUG_INC-Event (Parameter: 0)
Counterclockwise turn	Send HEADING_BUG_DEC-Event (Parameter: 0)

Approach mode	
----------------------	--

A32NX FBW MSFS2020

Button pressed for a short time (< 1 s)	Send AP_APR_HOLD-Event (Parameter: 0)
Change Buttonlight	
[LVAR:A32NX_FCU_APPR_MODE_ACTIVE] == 0	Switch Multi Panel APR to Shortmode OFF
[LVAR:A32NX_FCU_APPR_MODE_ACTIVE] == 1	Switch Multi Panel APR to Shortmode ON (permanent on)

Heading hold	
Button pressed for a short time (< 1 s)	Send FCU HDG PULL-Event (Parameter: 0)
Change Buttonlight	
(([LVAR:A32NX_FMA_LATERAL_MODE] != 10) && ([LVAR:A32NX_FMA_LATERAL_MODE] != 11))	Switch Multi Panel Heading to Shortmode OFF
(([LVAR:A32NX_FMA_LATERAL_MODE] == 10) ([LVAR:A32NX_FMA_LATERAL_MODE] == 11))	Switch Multi Panel Heading to Shortmode ON (permanent on)

Glideslope / reverse approach	
Button pressed for a short time (< 1 s)	Send FCU LOC PUSH-Event (Parameter: 0)
Change Buttonlight	
[LVAR:A32NX_FCU_LOC_MODE_ACTIVE] == 1	Switch Multi Panel GS / REV to Shortmode ON (permanent on)
[LVAR:A32NX_FCU_LOC_MODE_ACTIVE] != 1	Switch Multi Panel GS / REV to Shortmode OFF

NAV/CRS hold	
Button pressed for a short time (< 1 s)	Send FCU HDG PUSH-Event (Parameter: 0)
Change Buttonlight	
[LVAR:A32NX_FMA_LATERAL_MODE] == 20	Switch Multi Panel NAV / CRS to Shortmode ON (permanent on)
[LVAR:A32NX_FMA_LATERAL_MODE] != 20	Switch Multi Panel NAV / CRS to Shortmode OFF

IAS hold	
Button pressed for a short time (< 1 s)	Send FCU SPD PULL-Event (Parameter: 0)
Button pressed for a longer time (> 1s)	Send FCU SPD PUSH-Event (Parameter: 0)
Change Buttonlight	
[MSFS:AUTOPILOT SPEED SLOT INDEX] == 1	Switch Multi Panel IAS to Shortmode ON (permanent on)
[MSFS:AUTOPILOT SPEED SLOT INDEX] != 1	Switch Multi Panel IAS to Shortmode OFF

Altitude Hold	
----------------------	--

A32NX FBW MSFS2020

Button pressed for a short time (< 1 s)	Send FCU ALT PULL-Event (Parameter: 0)
Button pressed for a longer time (> 1s)	Send FCU ALT PUSH-Event (Parameter: 0)
Change Buttonlight	
[LVAR:A32NX_FMA_VERTICAL_MODE] == 10	Switch Multi Panel ALT to Shortmode ON (permanent on)
[LVAR:A32NX_FMA_VERTICAL_MODE] != 10	Switch Multi Panel ALT to Shortmode OFF

V/S hold	
Button pressed for a short time (< 1 s)	Send FCU VS PULL-Event (Parameter: 0)
Button pressed for a longer time (> 1s)	Send FCU VS PUSH-Event (Parameter: 0)
Change Buttonlight	
[LVAR:A32NX_FMA_VERTICAL_MODE] == 14	Switch Multi Panel V/S to Shortmode ON (permanent on)
[LVAR:A32NX_FMA_VERTICAL_MODE] != 14	Switch Multi Panel V/S to Shortmode OFF

Autopilot on/off	
Shortmode has been activated	Send FCU AP1 PUSH-Event (Parameter: 0)
Shortmode has been deactivated	Send FCU AP1 PUSH-Event (Parameter: 0)
Change Buttonlight	
(([LVAR:A32NX_AUTOPILOT_1_ACTIVE] == 0) && ([LVAR:A32NX_AUTOPILOT_2_ACTIVE] == 0))	Switch Multi Panel Autopilot to Shortmode OFF
(([LVAR:A32NX_AUTOPILOT_1_ACTIVE] == 1) ([LVAR:A32NX_AUTOPILOT_2_ACTIVE] == 1))	Switch Multi Panel Autopilot to Shortmode ON (permanent on)

Autothrottle arm	
Switched ON	
	Set XMLVAR_SWITCH_OVHD_INTLT_SEATBELT_POSITION (LVAR) to 1 Set XMLVAR_SWITCH_OVHD_INTLT_NOSMOKING_POSITION (LVAR) to 1 Set XMLVAR_SWITCH_OVHD_INTLT_EMEREXIT_POSITION (LVAR) to 1
[SIMCONNECT:CABIN SEATBELTS ALERT SWITCH] == 0	Send CABIN_SEATBELTS_ALERT_SWITCH_TOGGLE-Event (Parameter: 0)
Switched OFF [SIMCONNECT:CABIN SEATBELTS ALERT SWITCH] == 1	Send CABIN_SEATBELTS_ALERT_SWITCH_TOGGLE-Event (Parameter: 0)

Selector: ALT	
Display Value	Display AUTOPILOT ALTITUDE LOCK VAR:3

A32NX FBW MSFS2020

Clockwise turn	Send FCU ALT INC-Event (Parameter: 0)
Counterclockwise turn	Send FCU ALT DEC-Event (Parameter: 0)

Selector: VS	
Display Value	
[LVAR:A32NX_TRK_FPA_MODE_ACTIVE] == 0	Display A32NX_AUTOPILOT_VS_SELECTED (LVAR)
[LVAR:A32NX_TRK_FPA_MODE_ACTIVE] == 1	Display A32NX_AUTOPILOT_FPA_SELECTED (LVAR) Format 'F2'
Clockwise turn	Send AP_VS_VAR_INC-Event (Parameter: 0)
Counterclockwise turn	Send AP_VS_VAR_DEC-Event (Parameter: 0)

Selector: IAS	
Display Value	
Clockwise turn	Send AP_SPD_VAR_INC-Event (Parameter: 0)
Counterclockwise turn	Send AP_SPD_VAR_DEC-Event (Parameter: 0)

Pro Switch Panel (Pro Switch Panel)

Gear UP/DOWN	
Gear UP	Set GEAR HANDLE POSITION to 0
Gear DOWN	Set GEAR HANDLE POSITION to 1

Center/Nose Gear LED	
Change LED Color	
[SIMCONNECT:GEAR CENTER POSITION] == 0	Change Pro Switch Panel Nose/Center Gear Led to Off
[SIMCONNECT:GEAR CENTER POSITION] == 100	Change Pro Switch Panel Nose/Center Gear Led to Green
[SIMCONNECT:GEAR CENTER POSITION] < 100	Change Pro Switch Panel Nose/Center Gear Led to Red

Right Gear LED	
Change LED Color	
[SIMCONNECT:GEAR RIGHT POSITION] == 0	Change Pro Switch Panel Right Gear Led to Off
[SIMCONNECT:GEAR RIGHT POSITION] == 100	Change Pro Switch Panel Right Gear Led to Green
[SIMCONNECT:GEAR RIGHT POSITION] < 100	Change Pro Switch Panel Right Gear Led to Red

Left Gear LED	
Change LED Color	
[SIMCONNECT:GEAR LEFT POSITION] == 0	Change Pro Switch Panel Left Gear Led to Off
[SIMCONNECT:GEAR LEFT POSITION] == 100	Change Pro Switch Panel Left Gear Led to Green
[SIMCONNECT:GEAR LEFT POSITION] < 100	Change Pro Switch Panel Left Gear Led to Red

Power configuration	
Actions that can control the device's virtual power	
[SIMCONNECT:ELECTRICAL MASTER BATTERY] == 1	Send command Device: Virtual Power ON to Pro Switch Panel
[SIMCONNECT:ELECTRICAL MASTER BATTERY] == 0	Send command Device: Virtual Power OFF to Pro Switch Panel

Master Alternator

A32NX FBW MSFS2020

Switched ON [SIMCONNECT:GENERAL ENG MASTER ALTERNATOR:1] == 0	Set GENERAL ENG MASTER ALTERNATOR:1 to 1 Set GENERAL ENG MASTER ALTERNATOR:2 to 1 Set GENERAL ENG MASTER ALTERNATOR:3 to 1 Set GENERAL ENG MASTER ALTERNATOR:4 to 1
Switched OFF [SIMCONNECT:GENERAL ENG MASTER ALTERNATOR:1] == 1	Set GENERAL ENG MASTER ALTERNATOR:1 to 0 Set GENERAL ENG MASTER ALTERNATOR:2 to 0 Set GENERAL ENG MASTER ALTERNATOR:3 to 0 Set GENERAL ENG MASTER ALTERNATOR:4 to 0

Magneto/Engine starter switch	
OFF Position set [MSFS:EXTERNAL POWER ON] != 0	Send TOGGLE_EXTERNAL_POWER-Event (Parameter: 1)
R Position set [MSFS:EXTERNAL POWER ON] != 1	Send TOGGLE_EXTERNAL_POWER-Event (Parameter: 1)

De-Ice	
Switched ON	
[SIMCONNECT:STRUCTURAL DEICE SWITCH] != 1	Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_WING_PRESSED (LVAR) to 1 Send TOGGLE_STRUCTURAL_DEICE-Event (Parameter: 0)
[SIMCONNECT:ENG ANTI ICE:1] != 1	Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_ENG1_PRESSED (LVAR) to 1 Send ANTI_ICE_TOGGLE_ENG1-Event (Parameter: 0)
[SIMCONNECT:ENG ANTI ICE:2] != 1	Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_ENG2_PRESSED (LVAR) to 1 Send ANTI_ICE_TOGGLE_ENG2-Event (Parameter: 0)
Switched OFF	
[SIMCONNECT:STRUCTURAL DEICE SWITCH] != 0	Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_WING_PRESSED (LVAR) to 0 Send TOGGLE_STRUCTURAL_DEICE-Event (Parameter: 0)
[SIMCONNECT:ENG ANTI ICE:1] != 0	Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_ENG1_PRESSED (LVAR) to 0 Send ANTI_ICE_TOGGLE_ENG1-Event (Parameter: 0)
[SIMCONNECT:ENG ANTI ICE:2] != 0	Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_ENG2_PRESSED (LVAR) to 0 Send ANTI_ICE_TOGGLE_ENG2-Event (Parameter: 0)

Pitot Heat	
Switched ON	Set XMLVAR_MOMENTARY_PUSH_OVHD_PROBESWINDOW_PRESSED (LVAR) to 1 Set A32NX_MAN_PITOT_HEAT (LVAR) to 1

Switched OFF	Set XMLVAR_MOMENTARY_PUSH_OVHD_PROBESWINDOW_PRESSED (LVAR) to 0 Set A32NX_MAN_PITOT_HEAT (LVAR) to 0
--------------	---

Panel Lights	
Switched ON	Send PANEL_LIGHTS_ON-Event (Parameter: 0) Set LIGHT POTENTIOMETER:86 to 100 Set LIGHT POTENTIOMETER:88 to 99 Set LIGHT POTENTIOMETER:89 to 99 Set LIGHT POTENTIOMETER:94 to 10 Set LIGHT POTENTIOMETER:84 to 99 Set LIGHT POTENTIOMETER:87 to 99 Set LIGHT POTENTIOMETER:91 to 99 Set LIGHT POTENTIOMETER:90 to 99 Set LIGHT POTENTIOMETER:95 to 10 Set LIGHT POTENTIOMETER:85 to 99 Set LIGHT POTENTIOMETER:83 to 10 Set LIGHT POTENTIOMETER:76 to 10 Set A32NX_BARO_BRIGHTNESS (LVAR) to 0.9 Set A32NX_MCDU_L_BRIGHTNESS (LVAR) to 0.9 Set A32NX_MCDU_R_BRIGHTNESS (LVAR) to 0.9 Set LIGHT POTENTIOMETER:92 to 99 Set LIGHT POTENTIOMETER:93 to 99

A32NX FBW MSFS2020

Switched OFF	Set LIGHT POTENTIOMETER:86 to 0 Set LIGHT POTENTIOMETER:88 to 10 Set LIGHT POTENTIOMETER:89 to 10 Set LIGHT POTENTIOMETER:94 to 10 Set LIGHT POTENTIOMETER:84 to 0 Set LIGHT POTENTIOMETER:87 to 0 Set LIGHT POTENTIOMETER:91 to 10 Set LIGHT POTENTIOMETER:90 to 10 Set LIGHT POTENTIOMETER:95 to 10 Set LIGHT POTENTIOMETER:85 to 0 Set LIGHT POTENTIOMETER:83 to 0 Set LIGHT POTENTIOMETER:76 to 0 Set A32NX_BARO_BRIGHTNESS (LVAR) to 0.1 Set A32NX_MCDU_L_BRIGHTNESS (LVAR) to 0.05 Set A32NX_MCDU_R_BRIGHTNESS (LVAR) to 0.05 Set LIGHT POTENTIOMETER:92 to 10 Set LIGHT POTENTIOMETER:93 to 10
--------------	---

Cowl	
Switched ON [SIMCONNECT:LIGHT CABIN] == 0	Send TOGGLE_CABIN_LIGHTS-Event (Parameter: 0) Set LIGHT POTENTIOMETER:7 to 50
Switched OFF [SIMCONNECT:LIGHT CABIN] == 1	Send TOGGLE_CABIN_LIGHTS-Event (Parameter: 0) Set LIGHT POTENTIOMETER:7 to 0

Strobe	
Switched ON	Send STROBES_ON-Event (Parameter: 0) Set STROBE_1_AUTO (LVAR) to 1
Switched OFF	Send STROBES_OFF-Event (Parameter: 0) Set STROBE_1_AUTO (LVAR) to 0

Beacon	
Switched ON	Send BEACON_LIGHTS_SET-Event (Parameter: 1)
Switched OFF	Send BEACON_LIGHTS_SET-Event (Parameter: 0)

A32NX FBW MSFS2020

Nav	
Switched ON	Send NAV_LIGHTS_SET-Event (Parameter: 1) Send LOGO_LIGHTS_SET-Event (Parameter: 1) Set LIGHT WING to 1
Switched OFF	Send NAV_LIGHTS_SET-Event (Parameter: 0) Send LOGO_LIGHTS_SET-Event (Parameter: 0) Set LIGHT WING to 0

Master Battery	
Switched ON	Set A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO (LVAR) to 1 Delay execution for 500 ms. Set A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO (LVAR) to 1
Switched OFF	Set A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO (LVAR) to 0 Delay execution for 500 ms. Set A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO (LVAR) to 0

Fuel Pump	
Switched ON [MSFS:FUELSYSTEM PUMP ACTIVE:2] != 1	Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 1) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 2) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 3) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 4) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 5) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 6)
Switched OFF [MSFS:FUELSYSTEM PUMP ACTIVE:1] != 0	Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 1) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 2) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 3) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 4) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 5) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 6)

Avionics Master

A32NX FBW MSFS2020

Switched ON [SIMCONNECT:AVIONICS MASTER SWITCH] == 0	Send AVIONICS_MASTER_SET-Event (Parameter: 1) Set A32NX_OVHD_ADIRS_IR_1_MODE_SELECTOR_KNOB (LVAR) to 1 Set A32NX_OVHD_ADIRS_IR_2_MODE_SELECTOR_KNOB (LVAR) to 1 Set A32NX_OVHD_ADIRS_IR_3_MODE_SELECTOR_KNOB (LVAR) to 1 Set PUSH_OVHD_OXYGEN_CREW (LVAR) to 0
Switched OFF [SIMCONNECT:AVIONICS MASTER SWITCH] == 1	Send AVIONICS_MASTER_SET-Event (Parameter: 0) Set A32NX_OVHD_ADIRS_IR_1_MODE_SELECTOR_KNOB (LVAR) to 0 Set A32NX_OVHD_ADIRS_IR_2_MODE_SELECTOR_KNOB (LVAR) to 0 Set A32NX_OVHD_ADIRS_IR_3_MODE_SELECTOR_KNOB (LVAR) to 0 Set PUSH_OVHD_OXYGEN_CREW (LVAR) to 1

Taxi	
Switched ON	Send TAXI_LIGHTS_SET-Event (Parameter: 1)
Switched OFF	Send TAXI_LIGHTS_SET-Event (Parameter: 0)

Landing	
Switched ON	Send LANDING_LIGHTS_TOGGLE-Event (Parameter: 2) Send LANDING_LIGHTS_TOGGLE-Event (Parameter: 3) Set LANDING_2_RETRACTED (LVAR) to 0 Set LANDING_3_RETRACTED (LVAR) to 0
Switched OFF	Send LANDING_LIGHTS_OFF-Event (Parameter: 0) Set LANDING_2_RETRACTED (LVAR) to 1 Set LANDING_3_RETRACTED (LVAR) to 1
Scripted event ([LOCAL:SWITCH_TAXI_LIGHTS] == 1) && ([LOCAL:SWITCH_LANDING_LIGHTS] == 1)	Send TAXI_LIGHTS_SET-Event (Parameter: 0) Send LANDING_LIGHTS_SET-Event (Parameter: 1)

Script Panel (Script Panel)

SCRIPT Row 1 Col 1 (TouchdownFPM)	
Conditional Action	
([SIMCONNECT:SIM ON GROUND] == 1) && ([LOCAL:TOUCHDOWNFPMRESET] == 0)	Say ' [FSUIPC:0000:030C,CONV=FEET PER MINUTE=>FEET PER SECOND] ' Set TOUCHDOWNFPMRESET (Session) to 1
([LOCAL:TOUCHDOWNFPMRESET] == 1) && ([SIMCONNECT:SIM ON GROUND] == 0)	Set TOUCHDOWNFPMRESET (Session) to 0

SCRIPT Row 1 Col 2 (SpeedCallOuts)	
Conditional Action	
([SIMCONNECT:SIM ON GROUND] == 1) && ([SIMCONNECT:GROUND VELOCITY] > 80) && ([SIMCONNECT:GROUND VELOCITY] < 85)	Say '80'
([SIMCONNECT:SIM ON GROUND] == 1) && ([SIMCONNECT:GROUND VELOCITY] > 100) && ([SIMCONNECT:GROUND VELOCITY] < 105)	Say '100'
([SIMCONNECT:SIM ON GROUND] == 1) && ([SIMCONNECT:GROUND VELOCITY] > [LVAR:AIRLINER_V1_SPEED]) && ([SIMCONNECT:GROUND VELOCITY] < [LVAR:AIRLINER_VR_SPEED]) && ([SIMCONNECT:GROUND VELOCITY] > 120)	Say 'V 1'
([SIMCONNECT:SIM ON GROUND] == 1) && ([SIMCONNECT:GROUND VELOCITY] > [LVAR:AIRLINER_VR_SPEED]) && ([SIMCONNECT:GROUND VELOCITY] < [LVAR:AIRLINER_V2_SPEED]) && ([SIMCONNECT:GROUND VELOCITY] > 120)	Say 'Rotate'

TCA Q-Eng 1&2 (TCA-Q Right Addon)

X AXIS (Left Thrust Lever)	
Axis change	Axis Range 0-65535 CONTROL THROTTLE1_AXIS_SET_EX1 [axisvalue raw]
Button pressed	Send AUTO_THROTTLE_ARM-Event (Parameter: 0)

Y AXIS (Right Thrust Lever)	
Axis change	Axis Range 0-65535 CONTROL THROTTLE2_AXIS_SET_EX1 [axisvalue raw]
Button pressed	Send AUTO_THROTTLE_ARM-Event (Parameter: 0)

BUTTON_3 (Left Engine Switch)	
Switched ON	Send ENGINE_MASTER_1_SET-Event (Parameter: 1) Send FUELSYSTEM_VALVE_OPEN-Event (Parameter: 1) Send STARTER1_SET-Event (Parameter: 1)
Switched OFF	Send STARTER1_SET-Event (Parameter: 0) Send FUELSYSTEM_VALVE_CLOSE-Event (Parameter: 1) Send ENGINE_MASTER_1_SET-Event (Parameter: 0)

BUTTON_4 (Right Engine Switch)	
Switched ON	Send ENGINE_MASTER_2_SET-Event (Parameter: 1) Send FUELSYSTEM_VALVE_OPEN-Event (Parameter: 2) Send STARTER2_SET-Event (Parameter: 1)
Switched OFF	Send STARTER2_SET-Event (Parameter: 0) Send FUELSYSTEM_VALVE_CLOSE-Event (Parameter: 2) Send ENGINE_MASTER_2_SET-Event (Parameter: 0)

Engine Mode (Engine Mode)	
Crank mode	Send TURBINE_IGNITION_SWITCH_SET-Event (Parameter: 0)
Norm mode	Send TURBINE_IGNITION_SWITCH_SET1-Event (Parameter: 1) Send TURBINE_IGNITION_SWITCH_SET2-Event (Parameter: 1)
Ignition mode	Send TURBINE_IGNITION_SWITCH_SET1-Event (Parameter: 2) Send TURBINE_IGNITION_SWITCH_SET2-Event (Parameter: 2)

BUTTON_6 (Fire/Fault Right)	
Button pressed	Send AP_MASTER-Event (Parameter: 0)

BUTTON_21 (Gear)	
Gear UP	Set GEAR HANDLE POSITION to 0
Gear DOWN	Set GEAR HANDLE POSITION to 1

Z_AXIS (Flaps)	
Axis change	Flaps (auto-detent)

BUTTON_20 (Park Brake)	
Switched ON	Set A32NX_PARK_BRAKE_LEVER_POS (LVAR) to 1
Switched OFF	Set A32NX_PARK_BRAKE_LEVER_POS (LVAR) to 0

RUDDERTRIM	
Scripted event	
[LOCAL:JOY_0X044F0X0407_BUTTON_18] == 1	Set XMLVAR_RUDDERTRIM (LVAR) to 0
[LOCAL:JOY_0X044F0X0407_BUTTON_19] == 1	Set XMLVAR_RUDDERTRIM (LVAR) to 2

BUTTON_17 (Button 17)	
Button pressed	Send RUDDER_TRIM_SET-Event (Parameter: 0)

Autobrake (Autobrake)	
Autobrake Disarm	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 0
Autobrake Lo	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 1
Autobrake 2	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 2
Autobrake 3	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 2
Autobrake Hi	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 3

RZ_AXIS (Speedbrake)	
Axis change	Axis Range 0-65535 CONTROL SPOILERS_SET [axisvalue raw]

BUTTON_5 (Fire/Fault Left)	
Button pressed	Send SPOILERS_ARM_TOGGLE-Event (Parameter: 0)

Streamdeck (Stream Deck XL (CL10K1A11126))

Page: MAIN ({c119d64f-ec70-43f5-be87-3d5ca51ee160})

Row 1 Button 1	
Button pressed for a short time (< 1 s)	Press and release F9 for 50ms

Row 1 Button 2	
Button pressed for a short time (< 1 s)	Press and release LControlKey + D1 for 50ms

Row 1 Button 3	
Button pressed for a short time (< 1 s)	Press and release LMenu + D1 for 50ms

Row 1 Button 4	
Button pressed for a short time (< 1 s)	Press and release LControlKey + D8 for 50ms

Row 1 Button 5	
Button pressed for a short time (< 1 s)	Press and release LMenu + D2 for 50ms

Row 1 Button 6	
-----------------------	--

Row 1 Button 7	
-----------------------	--

Row 1 Button 8	
Button pressed for a short time (< 1 s)	Device: Switch to page/gauge OVHD

Row 2 Button 1	
Button released	Press and release LControlKey + D0 for 50ms

Row 2 Button 2	
-----------------------	--

Row 2 Button 3	
-----------------------	--

Row 2 Button 4

Row 2 Button 5

Row 2 Button 6

Row 2 Button 7

Row 2 Button 8

Button pressed for a short time (< 1 s)

Device: Switch to page/gauge FCU

Row 3 Button 1

Row 3 Button 2

Row 3 Button 3

Row 3 Button 4

Row 3 Button 5

Row 3 Button 6

Row 3 Button 7

Row 3 Button 8

Button pressed for a short time (< 1 s)

Device: Switch to page/gauge Pedestal

Row 4 Button 1

Row 4 Button 2

Row 4 Button 3	
Button pressed for a short time (< 1 s)	Send SIM_RATE_DECR-Event (Parameter: 0)
Row 4 Button 4	
Change Label [SIMCONNECT:SIMULATION RATE] != 0	Change [i]Stream Deck XL (CL10K1A11126)[/i] [b]Row 4 Button 4[/b] to [b]!#('SIM RATE'+'\r\n'+[SIMCONNECT:SIMULATION RATE])[/b]
Row 4 Button 5	
Button pressed for a short time (< 1 s)	Send SIM_RATE_INCR-Event (Parameter: 0)
Row 4 Button 6	
Row 4 Button 7	
Change Label [LOCAL:FRAMERATE] != 0	Change [i]Stream Deck XL (CL10K1A11126)[/i] [b]Row 4 Button 7[/b] to [b]!#('FPS'+'\r\n'+[LOCAL:FRAMERATE])[/b]
Row 4 Button 8	
Button pressed for a short time (< 1 s)	Device: Switch to page/gauge MAIN

Row 1 Button 1	
Change Image	
[LVAR:A32NX_OVHD_ADIRS_IR_1_MODE_SELECTOR_KNOB] == 1	Change Stream Deck XL (CL10K1A11126) Row 1 Button 1 to ADIR_ON(Profile)
[LVAR:A32NX_OVHD_ADIRS_IR_1_MODE_SELECTOR_KNOB] == 0	Change Stream Deck XL (CL10K1A11126) Row 1 Button 1 to ADIR_OFF(Profile)
Button pressed for a short time (< 1 s)	
[SIMCONNECT:AVIONICS MASTER SWITCH] == 0	Send AVIONICS_MASTER_SET-Event (Parameter: 1) Set A32NX_OVHD_ADIRS_IR_1_MODE_SELECTOR_KNOB (LVAR) to 1 Set A32NX_OVHD_ADIRS_IR_2_MODE_SELECTOR_KNOB (LVAR) to 1 Set A32NX_OVHD_ADIRS_IR_3_MODE_SELECTOR_KNOB (LVAR) to 1
[SIMCONNECT:AVIONICS MASTER SWITCH] == 1	Send AVIONICS_MASTER_SET-Event (Parameter: 0) Set A32NX_OVHD_ADIRS_IR_1_MODE_SELECTOR_KNOB (LVAR) to 0 Set A32NX_OVHD_ADIRS_IR_2_MODE_SELECTOR_KNOB (LVAR) to 0 Set A32NX_OVHD_ADIRS_IR_3_MODE_SELECTOR_KNOB (LVAR) to 0

Row 1 Button 2	
Change Image	
[LVAR:PUSH_OVHD_OXYGEN_CREW] == 1	Change Stream Deck XL (CL10K1A11126) Row 1 Button 2 to A320_Button_white_off(Profile)
[LVAR:PUSH_OVHD_OXYGEN_CREW] == 0	Change Stream Deck XL (CL10K1A11126) Row 1 Button 2 to A320_Button_white_on(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:PUSH_OVHD_OXYGEN_CREW] == 0	Set PUSH_OVHD_OXYGEN_CREW (LVAR) to 1
[LVAR:PUSH_OVHD_OXYGEN_CREW] == 1	Set PUSH_OVHD_OXYGEN_CREW (LVAR) to 0

Row 1 Button 3	
Button pressed for a short time (< 1 s)	Set PUSH_OVHD_CALLS_ALL (LVAR) to 1 Delay execution for 500 ms. Set PUSH_OVHD_CALLS_ALL (LVAR) to 0

Row 1 Button 4	
Change Image	

A32NX FBW MSFS2020

([LVAR:A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO] == 0) && ([LVAR:A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO] == 1)	Change Stream Deck XL (CL10K1A11126) Row 1 Button 4 to A320_Button_white_off(Profile)
([LVAR:A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO] == 0) && ([LVAR:A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO] == 0)	Change Stream Deck XL (CL10K1A11126) Row 1 Button 4 to A320_Button_white_on(Profile)
([LVAR:A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO] == 1) && ([LVAR:A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO] == 1)	Change Stream Deck XL (CL10K1A11126) Row 1 Button 4 to A320_Button_white_on(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO] == 0	Set A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO (LVAR) to 1
[LVAR:A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO] == 1	Set A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO (LVAR) to 0

Row 1 Button 5	
Change Image	
([LVAR:A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO] == 1) && ([LVAR:A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO] == 0)	Change Stream Deck XL (CL10K1A11126) Row 1 Button 5 to A320_Button_white_off(Profile)
([LVAR:A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO] == 0) && ([LVAR:A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO] == 0)	Change Stream Deck XL (CL10K1A11126) Row 1 Button 5 to A320_Button_white_on(Profile)
([LVAR:A32NX_OVHD_ELEC_BAT_1_PB_IS_AUTO] == 1) && ([LVAR:A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO] == 1)	Change Stream Deck XL (CL10K1A11126) Row 1 Button 5 to A320_Button_white_on(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO] == 0	Set A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO (LVAR) to 1
[LVAR:A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO] == 1	Set A32NX_OVHD_ELEC_BAT_2_PB_IS_AUTO (LVAR) to 0

Row 1 Button 6	
Change Image	
[MSFS:FUELSYSTEM PUMP ACTIVE:2] == 0	Change Stream Deck XL (CL10K1A11126) Row 1 Button 6 to A320_Button_white_off(Profile)
[MSFS:FUELSYSTEM PUMP ACTIVE:2] == 1	Change Stream Deck XL (CL10K1A11126) Row 1 Button 6 to A320_Button_white_on(Profile)
Button pressed for a short time (< 1 s)	
[MSFS:FUELSYSTEM PUMP ACTIVE:2] == [MSFS:FUELSYSTEM PUMP ACTIVE:5]	Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 2) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 5)
[MSFS:FUELSYSTEM PUMP ACTIVE:2] != [MSFS:FUELSYSTEM PUMP ACTIVE:5]	Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 2)

Row 1 Button 7	
-----------------------	--

Change Image	
[MSFS:FUELSYSTEM PUMP SWITCH:1] == 0	Change Stream Deck XL (CL10K1A11126) Row 1 Button 7 to A320_Button_white_off(Profile)
[MSFS:FUELSYSTEM PUMP SWITCH:1] == 1	Change Stream Deck XL (CL10K1A11126) Row 1 Button 7 to A320_Button_white_on(Profile)
Button pressed for a short time (< 1 s)	
[MSFS:FUELSYSTEM PUMP SWITCH:1] == [MSFS:FUELSYSTEM PUMP SWITCH:4]	Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 1) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 4)
[MSFS:FUELSYSTEM PUMP SWITCH:1] != [MSFS:FUELSYSTEM PUMP SWITCH:4]	Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 1)

Row 1 Button 8	
Change Image	
[MSFS:FUELSYSTEM PUMP ACTIVE:3] == 0	Change Stream Deck XL (CL10K1A11126) Row 1 Button 8 to A320_Button_white_off(Profile)
[MSFS:FUELSYSTEM PUMP ACTIVE:3] == 1	Change Stream Deck XL (CL10K1A11126) Row 1 Button 8 to A320_Button_white_on(Profile)
Button pressed for a short time (< 1 s)	
[MSFS:FUELSYSTEM PUMP ACTIVE:3] == [MSFS:FUELSYSTEM PUMP ACTIVE:6]	Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 3) Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 6)
[MSFS:FUELSYSTEM PUMP ACTIVE:3] != [MSFS:FUELSYSTEM PUMP ACTIVE:6]	Send FUELSYSTEM_PUMP_TOGGLE-Event (Parameter: 3)

Row 2 Button 1	
Change Image	
[SIMCONNECT:STRUCTURAL DEICE SWITCH] == 0	Change Stream Deck XL (CL10K1A11126) Row 2 Button 1 to A320_Button_blue_off(Profile)
[SIMCONNECT:STRUCTURAL DEICE SWITCH] == 1	Change Stream Deck XL (CL10K1A11126) Row 2 Button 1 to A320_Button_blue_on(Profile)
Button pressed for a short time (< 1 s)	
[SIMCONNECT:STRUCTURAL DEICE SWITCH] == 0	Send TOGGLE_STRUCTURAL_DEICE-Event (Parameter: 0) Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_WING_PRESSED (LVAR) to 1
[SIMCONNECT:STRUCTURAL DEICE SWITCH] == 1	Send TOGGLE_STRUCTURAL_DEICE-Event (Parameter: 0) Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_WING_PRESSED (LVAR) to 0

Row 2 Button 2	
Change Image	
[SIMCONNECT:ENG ANTI ICE:1] == 0	Change Stream Deck XL (CL10K1A11126) Row 2 Button 2 to A320_Button_blue_off(Profile)
[SIMCONNECT:ENG ANTI ICE:1] == 1	Change Stream Deck XL (CL10K1A11126) Row 2 Button 2 to A320_Button_blue_on(Profile)

A32NX FBW MSFS2020

Button pressed for a short time (< 1 s)	
[SIMCONNECT:ENG ANTI ICE:1] == 0	Send ANTI_ICE_TOGGLE_ENG1-Event (Parameter: 0) Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_ENG1_PRESSED (LVAR) to 1
[SIMCONNECT:ENG ANTI ICE:1] == 1	Send ANTI_ICE_TOGGLE_ENG1-Event (Parameter: 0) Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_ENG1_PRESSED (LVAR) to 0

Row 2 Button 3	
Change Image	
[SIMCONNECT:ENG ANTI ICE:2] == 0	Change Stream Deck XL (CL10K1A11126) Row 2 Button 3 to A320_Button_blue_off(Profile)
[SIMCONNECT:ENG ANTI ICE:2] == 1	Change Stream Deck XL (CL10K1A11126) Row 2 Button 3 to A320_Button_blue_on(Profile)
Button pressed for a short time (< 1 s)	
[SIMCONNECT:ENG ANTI ICE:2] == 0	Send ANTI_ICE_TOGGLE_ENG2-Event (Parameter: 0) Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_ENG2_PRESSED (LVAR) to 1
[SIMCONNECT:ENG ANTI ICE:2] == 1	Send ANTI_ICE_TOGGLE_ENG2-Event (Parameter: 0) Set XMLVAR_MOMENTARY_PUSH_OVHD_ANTIICE_ENG2_PRESSED (LVAR) to 0

Row 2 Button 4	
Change Image	
[LVAR:A32NX_OVHD_PNEU_APU_BLEED_PB_IS_ON] == 1	Change Stream Deck XL (CL10K1A11126) Row 2 Button 4 to A320_Button_blue_on(Profile)
[LVAR:A32NX_OVHD_PNEU_APU_BLEED_PB_IS_ON] == 0	Change Stream Deck XL (CL10K1A11126) Row 2 Button 4 to A320_Button_blue_off(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_OVHD_PNEU_APU_BLEED_PB_IS_ON] == 0	Set A32NX_OVHD_PNEU_APU_BLEED_PB_IS_ON (LVAR) to 1
[LVAR:A32NX_OVHD_PNEU_APU_BLEED_PB_IS_ON] == 1	Set A32NX_OVHD_PNEU_APU_BLEED_PB_IS_ON (LVAR) to 0

Row 2 Button 5	
Change Image	
([MSFS:EXTERNAL POWER AVAILABLE] == 1) && ([MSFS:EXTERNAL POWER ON] == 0)	Change Stream Deck XL (CL10K1A11126) Row 2 Button 5 to AVAIL(Profile)
([MSFS:EXTERNAL POWER ON] == 1) && ([MSFS:EXTERNAL POWER AVAILABLE] == 1)	Change Stream Deck XL (CL10K1A11126) Row 2 Button 5 to A320_Button_blue_on(Profile)
([MSFS:EXTERNAL POWER AVAILABLE] == 0) && ([MSFS:EXTERNAL POWER ON] == 0)	Change Stream Deck XL (CL10K1A11126) Row 2 Button 5 to A320_Button_blue_off(Profile)
Button pressed for a short time (< 1 s)	
Send TOGGLE_EXTERNAL_POWER-Event (Parameter: 0)	

Row 2 Button 6	
Change Image	
([LVAR:A32NX_OVHD_ELEC_ENG_GEN_1_PB_IS_ON] == 0) && ([LVAR:A32NX_OVHD_ELEC_ENG_GEN_1_PB_HAS_FAULT] == 0)	Change Stream Deck XL (CL10K1A11126) Row 2 Button 6 to A320_Button_white_off(Profile)
([LVAR:A32NX_OVHD_ELEC_ENG_GEN_1_PB_IS_ON] == 1) && ([LVAR:A32NX_OVHD_ELEC_ENG_GEN_1_PB_HAS_FAULT] == 0)	Change Stream Deck XL (CL10K1A11126) Row 2 Button 6 to A320_Button_white_on(Profile)
[LVAR:A32NX_OVHD_ELEC_ENG_GEN_1_PB_HAS_FAULT] == 1	Change Stream Deck XL (CL10K1A11126) Row 2 Button 6 to FAULT(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_OVHD_ELEC_ENG_GEN_1_PB_IS_ON] == 0	Set GENERAL ENG MASTER ALTERNATOR:1 to 1
[LVAR:A32NX_OVHD_ELEC_ENG_GEN_1_PB_IS_ON] == 1	Set GENERAL ENG MASTER ALTERNATOR:1 to 0

Row 2 Button 7	
Change Image	
([LVAR:A32NX_OVHD_ELEC_ENG_GEN_2_PB_IS_ON] == 0) && ([LVAR:A32NX_OVHD_ELEC_ENG_GEN_2_PB_HAS_FAULT] == 0)	Change Stream Deck XL (CL10K1A11126) Row 2 Button 7 to A320_Button_white_off(Profile)
([LVAR:A32NX_OVHD_ELEC_ENG_GEN_2_PB_IS_ON] == 1) && ([LVAR:A32NX_OVHD_ELEC_ENG_GEN_2_PB_HAS_FAULT] == 0)	Change Stream Deck XL (CL10K1A11126) Row 2 Button 7 to A320_Button_white_on(Profile)
[LVAR:A32NX_OVHD_ELEC_ENG_GEN_2_PB_HAS_FAULT] == 1	Change Stream Deck XL (CL10K1A11126) Row 2 Button 7 to FAULT(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_OVHD_ELEC_ENG_GEN_2_PB_IS_ON] == 0	Set GENERAL ENG MASTER ALTERNATOR:2 to 1
[LVAR:A32NX_OVHD_ELEC_ENG_GEN_2_PB_IS_ON] == 1	Set GENERAL ENG MASTER ALTERNATOR:2 to 0

Row 2 Button 8	
Change Image	
([LVAR:A32NX_OVHD_ELEC_APU_GEN_PB_IS_ON] == 0) && ([LVAR:A32NX_OVHD_ELEC_APU_GEN_PB_HAS_FAULT] == 0)	Change Stream Deck XL (CL10K1A11126) Row 2 Button 8 to A320_Button_white_off(Profile)
([LVAR:A32NX_OVHD_ELEC_APU_GEN_PB_IS_ON] == 1) && ([LVAR:A32NX_OVHD_ELEC_APU_GEN_PB_HAS_FAULT] == 0)	Change Stream Deck XL (CL10K1A11126) Row 2 Button 8 to A320_Button_white_on(Profile)
[LVAR:A32NX_OVHD_ELEC_APU_GEN_PB_HAS_FAULT] == 1	Change Stream Deck XL (CL10K1A11126) Row 2 Button 8 to FAULT(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_OVHD_ELEC_APU_GEN_PB_IS_ON] == 0	Set APU GENERATOR SWITCH to 1
[LVAR:A32NX_OVHD_ELEC_APU_GEN_PB_IS_ON] == 1	Set APU GENERATOR SWITCH to 0

Row 3 Button 1	
Change Image	
[SIMCONNECT:LIGHT STROBE] == 0	Change Stream Deck XL (CL10K1A11126) Row 3 Button 1 to A320_Light1_off(Profile)
[SIMCONNECT:LIGHT STROBE] == 1	Change Stream Deck XL (CL10K1A11126) Row 3 Button 1 to A320_Light1_on(Profile)
Button pressed for a short time (< 1 s)	
[SIMCONNECT:LIGHT STROBE] == 0	Send STROBES_SET-Event (Parameter: 1) Set STROBE_1_AUTO (LVAR) to 1
[SIMCONNECT:LIGHT STROBE] == 1	Set STROBE_1_AUTO (LVAR) to 0 Send STROBES_SET-Event (Parameter: 0)

Row 3 Button 2	
Change Image	
[LVAR:LANDING_2_RETRACTED] == 0	Change Stream Deck XL (CL10K1A11126) Row 3 Button 2 to A320_LightLL_on(Profile)
[LVAR:LANDING_2_RETRACTED] == 1	Change Stream Deck XL (CL10K1A11126) Row 3 Button 2 to A320_LightLL_off(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:LANDING_2_RETRACTED] == 1	Send LANDING_LIGHTS_TOGGLE-Event (Parameter: 2) Set LANDING_2_RETRACTED (LVAR) to 0
[LVAR:LANDING_2_RETRACTED] == 0	Send LANDING_LIGHTS_TOGGLE-Event (Parameter: 2) Set LANDING_2_RETRACTED (LVAR) to 1

Row 3 Button 3	
Change Image	
[LVAR:LANDING_3_RETRACTED] == 0	Change Stream Deck XL (CL10K1A11126) Row 3 Button 3 to A320_LightLL_on(Profile)
[LVAR:LANDING_3_RETRACTED] == 1	Change Stream Deck XL (CL10K1A11126) Row 3 Button 3 to A320_LightLL_off(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:LANDING_3_RETRACTED] == 1	Send LANDING_LIGHTS_TOGGLE-Event (Parameter: 3) Set LANDING_3_RETRACTED (LVAR) to 0
[LVAR:LANDING_3_RETRACTED] == 0	Send LANDING_LIGHTS_TOGGLE-Event (Parameter: 3) Set LANDING_3_RETRACTED (LVAR) to 1

Row 3 Button 4	
Change Image	

A32NX FBW MSFS2020

[LVAR:A32NX_OVHD_APU_MASTER_SW_PB_IS_ON] == 1	Change Stream Deck XL (CL10K1A11126) Row 3 Button 4 to A320_Button_blue_on(Profile)
[LVAR:A32NX_OVHD_APU_MASTER_SW_PB_IS_ON] == 0	Change Stream Deck XL (CL10K1A11126) Row 3 Button 4 to A320_Button_blue_off(Profile)
Button pressed for a short time (< 1 s) [LVAR:A32NX_OVHD_APU_MASTER_SW_PB_IS_ON] == 0	Set A32NX_OVHD_APU_MASTER_SW_PB_IS_ON (LVAR) to 1
Button released [LVAR:A32NX_OVHD_APU_MASTER_SW_PB_IS_ON] == 1	Set A32NX_OVHD_APU_MASTER_SW_PB_IS_ON (LVAR) to 0

Row 3 Button 5	
Change Image	
[SIMCONNECT:LIGHT NAV] == 0	Change Stream Deck XL (CL10K1A11126) Row 3 Button 5 to A320_Light1_off(Profile)
[SIMCONNECT:LIGHT NAV] == 1	Change Stream Deck XL (CL10K1A11126) Row 3 Button 5 to A320_Light1_on(Profile)
Button pressed for a short time (< 1 s)	
[SIMCONNECT:LIGHT NAV] == 0	Send NAV_LIGHTS_SET-Event (Parameter: 1) Send LOGO_LIGHTS_SET-Event (Parameter: 1)
[SIMCONNECT:LIGHT NAV] == 1	Send NAV_LIGHTS_SET-Event (Parameter: 0) Send LOGO_LIGHTS_SET-Event (Parameter: 0)

Row 3 Button 6	
Change Image	
[SIMCONNECT:LIGHT BEACON] == 0	Change Stream Deck XL (CL10K1A11126) Row 3 Button 6 to A320_Light1_off(Profile)
[SIMCONNECT:LIGHT BEACON] == 1	Change Stream Deck XL (CL10K1A11126) Row 3 Button 6 to A320_Light1_on(Profile)
Button pressed for a short time (< 1 s)	
[SIMCONNECT:LIGHT BEACON] == 0	Send BEACON_LIGHTS_SET-Event (Parameter: 1)
[SIMCONNECT:LIGHT BEACON] == 1	Send BEACON_LIGHTS_SET-Event (Parameter: 0)

Row 3 Button 7	
Change Image	
[SIMCONNECT:LIGHT CABIN] == 0	Change Stream Deck XL (CL10K1A11126) Row 3 Button 7 to A320_Light1_off(Profile)
[SIMCONNECT:LIGHT CABIN] == 1	Change Stream Deck XL (CL10K1A11126) Row 3 Button 7 to A320_Light1_on(Profile)
Button pressed for a short time (< 1 s)	
[SIMCONNECT:LIGHT CABIN] == 0	Send TOGGLE_CABIN_LIGHTS-Event (Parameter: 0) Set LIGHT POTENTIOMETER:7 to 50

A32NX FBW MSFS2020

([SIMCONNECT:LIGHT CABIN] == 1) && ([MSFS:LIGHT POTENTIOMETER:7] < 100)	Set LIGHT POTENTIOMETER:7 to 100
([SIMCONNECT:LIGHT CABIN] == 1) && ([MSFS:LIGHT POTENTIOMETER:7] > 50)	Set LIGHT POTENTIOMETER:7 to 0 Send TOGGLE_CABIN_LIGHTS-Event (Parameter: 0)

Row 3 Button 8	
Change Image	
[MSFS:LIGHT POTENTIOMETER:86] >= 10	Change Stream Deck XL (CL10K1A11126) Row 3 Button 8 to A320_Light1_on(Profile)
[MSFS:LIGHT POTENTIOMETER:86] < 10	Change Stream Deck XL (CL10K1A11126) Row 3 Button 8 to A320_Light1_off(Profile)
Button pressed for a short time (< 1 s)	
[MSFS:LIGHT POTENTIOMETER:86] < 10	Set LIGHT POTENTIOMETER:86 to 100 Set LIGHT POTENTIOMETER:88 to 99 Set LIGHT POTENTIOMETER:89 to 99 Set LIGHT POTENTIOMETER:94 to 10 Set LIGHT POTENTIOMETER:84 to 99 Set LIGHT POTENTIOMETER:87 to 99 Set LIGHT POTENTIOMETER:91 to 99 Set LIGHT POTENTIOMETER:90 to 99 Set LIGHT POTENTIOMETER:95 to 10 Set LIGHT POTENTIOMETER:85 to 99 Set LIGHT POTENTIOMETER:83 to 10 Set LIGHT POTENTIOMETER:76 to 10 Set A32NX_BARO_BRIGHTNESS (LVAR) to 0.9 Set A32NX_MCDU_L_BRIGHTNESS (LVAR) to 0.9 Set A32NX_MCDU_R_BRIGHTNESS (LVAR) to 0.9 Set LIGHT POTENTIOMETER:92 to 99 Set LIGHT POTENTIOMETER:93 to 99

A32NX FBW MSFS2020

[MSFS:LIGHT POTENTIOMETER:86] >= 10	Set LIGHT POTENTIOMETER:86 to 0 Set LIGHT POTENTIOMETER:88 to 10 Set LIGHT POTENTIOMETER:89 to 10 Set LIGHT POTENTIOMETER:94 to 10 Set LIGHT POTENTIOMETER:84 to 0 Set LIGHT POTENTIOMETER:87 to 0 Set LIGHT POTENTIOMETER:91 to 10 Set LIGHT POTENTIOMETER:90 to 10 Set LIGHT POTENTIOMETER:95 to 10 Set LIGHT POTENTIOMETER:85 to 0 Set LIGHT POTENTIOMETER:83 to 0 Set LIGHT POTENTIOMETER:76 to 0 Set A32NX_BARO_BRIGHTNESS (LVAR) to 0.1 Set A32NX_MCDU_L_BRIGHTNESS (LVAR) to 0.05 Set A32NX_MCDU_R_BRIGHTNESS (LVAR) to 0.05 Set LIGHT POTENTIOMETER:92 to 10 Set LIGHT POTENTIOMETER:93 to 10
-------------------------------------	---

Row 4 Button 1

Row 4 Button 2	
Change Image	
[MSFS:CIRCUIT SWITCH ON:21] == 1	Change Stream Deck XL (CL10K1A11126) Row 4 Button 2 to A320_Light1_on(Profile)
[MSFS:CIRCUIT SWITCH ON:21] == 0	Change Stream Deck XL (CL10K1A11126) Row 4 Button 2 to A320_Light1_off(Profile)
Button pressed for a short time (< 1 s)	
[MSFS:CIRCUIT SWITCH ON:21] == 0	Set CIRCUIT SWITCH ON:21 to 1 Set CIRCUIT SWITCH ON:22 to 1
[MSFS:CIRCUIT SWITCH ON:21] == 1	Set CIRCUIT SWITCH ON:21 to 0 Set CIRCUIT SWITCH ON:22 to 0

Row 4 Button 3	
Change Image	
([SIMCONNECT:LIGHT LANDING] == 0) && ([SIMCONNECT:LIGHT TAXI] == 0)	Change Stream Deck XL (CL10K1A11126) Row 4 Button 3 to A320_Light1_off(Profile)

A32NX FBW MSFS2020

([SIMCONNECT:LIGHT LANDING] == 1) ([SIMCONNECT:LIGHT TAXI] == 1)	Change Stream Deck XL (CL10K1A11126) Row 4 Button 3 to A320_Light1_on(Profile)
Change Label	
([SIMCONNECT:LIGHT LANDING] == 0) && ([SIMCONNECT:LIGHT TAXI] == 0)	Change Stream Deck XL (CL10K1A11126) Row 4 Button 3 to NOSE
([SIMCONNECT:LIGHT LANDING] == 0) && ([SIMCONNECT:LIGHT TAXI] == 1)	Change Stream Deck XL (CL10K1A11126) Row 4 Button 3 to TAXI
([SIMCONNECT:LIGHT LANDING] == 1) && ([SIMCONNECT:LIGHT TAXI] == 0)	Change Stream Deck XL (CL10K1A11126) Row 4 Button 3 to T.O.
Button pressed for a short time (< 1 s)	
([SIMCONNECT:LIGHT LANDING] == 0) && ([SIMCONNECT:LIGHT TAXI] == 0)	Send TOGGLE_TAXI_LIGHTS-Event (Parameter: 1)
([SIMCONNECT:LIGHT LANDING] == 0) && ([SIMCONNECT:LIGHT TAXI] == 1)	Send TOGGLE_TAXI_LIGHTS-Event (Parameter: 1) Send LANDING_LIGHTS_TOGGLE-Event (Parameter: 1)
([SIMCONNECT:LIGHT LANDING] == 1) && ([SIMCONNECT:LIGHT TAXI] == 0)	Send LANDING_LIGHTS_TOGGLE-Event (Parameter: 1)
([SIMCONNECT:LIGHT LANDING] == 1) && ([SIMCONNECT:LIGHT TAXI] == 1)	Send LANDING_LIGHTS_TOGGLE-Event (Parameter: 1) Send TOGGLE_TAXI_LIGHTS-Event (Parameter: 1)

Row 4 Button 4	
Change Image	
([LVAR:A32NX_OVHD_APU_START_PB_IS_ON] == 1) && ([LVAR:A32NX_OVHD_APU_START_PB_IS_AVAILABLE] == 0)	Change Stream Deck XL (CL10K1A11126) Row 4 Button 4 to A320_Button_blue_on(Profile)
[LVAR:A32NX_OVHD_APU_START_PB_IS_AVAILABLE] == 1	Change Stream Deck XL (CL10K1A11126) Row 4 Button 4 to AVAIL(Profile)
([LVAR:A32NX_OVHD_APU_START_PB_IS_AVAILABLE] == 0) && ([LVAR:A32NX_OVHD_APU_START_PB_IS_ON] == 0)	Change Stream Deck XL (CL10K1A11126) Row 4 Button 4 to A320_Button_blue_off(Profile)
Button pressed for a short time (< 1 s)	
([LVAR:A32NX_OVHD_APU_MASTER_SW_PB_IS_ON] == 1) && ([LVAR:A32NX_OVHD_APU_START_PB_IS_ON] == 0) && ([LVAR:A32NX_OVHD_APU_START_PB_IS_AVAILABLE] == 0)	Set A32NX_OVHD_APU_START_PB_IS_ON (LVAR) to 1

Row 4 Button 5	
Change Image	

A32NX FBW MSFS2020

[SIMCONNECT:CABIN SEATBELTS ALERT SWITCH] == 0	Change Stream Deck XL (CL10K1A11126) Row 4 Button 5 to A320_Light1_off(Profile)
[SIMCONNECT:CABIN SEATBELTS ALERT SWITCH] == 1	Change Stream Deck XL (CL10K1A11126) Row 4 Button 5 to A320_Light1_on(Profile)
Button pressed for a short time (< 1 s)	Send CABIN_SEATBELTS_ALERT_SWITCH_TOGGLE-Event (Parameter: 0)

Row 4 Button 6	
Change Image	
[LVAR:XMLVAR_SWITCH_OVHD_INTLT_NOSMOKING_POSITION] == 2	Change Stream Deck XL (CL10K1A11126) Row 4 Button 6 to A320_Light1_off(Profile)
[LVAR:XMLVAR_SWITCH_OVHD_INTLT_NOSMOKING_POSITION] == 1	Change Stream Deck XL (CL10K1A11126) Row 4 Button 6 to A320_Light1_on(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:XMLVAR_SWITCH_OVHD_INTLT_NOSMOKING_POSITION] != 1	Set XMLVAR_SWITCH_OVHD_INTLT_NOSMOKING_POSITION (LVAR) to 1
[LVAR:XMLVAR_SWITCH_OVHD_INTLT_NOSMOKING_POSITION] != 2	Set XMLVAR_SWITCH_OVHD_INTLT_NOSMOKING_POSITION (LVAR) to 2

Row 4 Button 7	
Change Image	
[LVAR:XMLVAR_SWITCH_OVHD_INTLT_EMEREXIT_POSITION] == 2	Change Stream Deck XL (CL10K1A11126) Row 4 Button 7 to A320_Light1_off(Profile)
[LVAR:XMLVAR_SWITCH_OVHD_INTLT_EMEREXIT_POSITION] == 1	Change Stream Deck XL (CL10K1A11126) Row 4 Button 7 to A320_Light1_on(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:XMLVAR_SWITCH_OVHD_INTLT_EMEREXIT_POSITION] != 1	Set XMLVAR_SWITCH_OVHD_INTLT_EMEREXIT_POSITION (LVAR) to 1
[LVAR:XMLVAR_SWITCH_OVHD_INTLT_EMEREXIT_POSITION] != 2	Set XMLVAR_SWITCH_OVHD_INTLT_EMEREXIT_POSITION (LVAR) to 2

Row 4 Button 8	
Button pressed for a short time (< 1 s)	Device: Switch to page/gauge MAIN

Row 1 Button 1	
Change Label	
[LVAR:XMLVAR_Baro1_Mode] == 1	Change [i]/[i] [b]_CONFIG[/b] to [b]!#('QNH'+ '\r\n\r\n'+ Round((MSFS:KOHLSMAN SETTING MB:1),0))/[b]
[LVAR:XMLVAR_Baro1_Mode] == 3	Change _CONFIG to QNH STD
Button pressed for a short time (< 1 s)	
[LVAR:XMLVAR_Baro1_Mode] == 1	Set XMLVAR_BARO1_MODE (LVAR) to 3
[LVAR:XMLVAR_Baro1_Mode] == 3	Set XMLVAR_BARO1_MODE (LVAR) to 1

Row 1 Button 2	
Button pressed for a short time (< 1 s)	
	Increment KOHLSMAN SETTING MB by 1

Row 1 Button 3	
Change Image	
[LVAR:BTN_CSTR_1_FILTER_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:BTN_CSTR_1_FILTER_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:BTN_CSTR_1_FILTER_ACTIVE] == 0	Set BTN_CSTR_1_FILTER_ACTIVE (LVAR) to 1
[LVAR:BTN_CSTR_1_FILTER_ACTIVE] == 1	Set BTN_CSTR_1_FILTER_ACTIVE (LVAR) to 0

Row 1 Button 4	
Change Image	
[LVAR:BTN_VORD_1_FILTER_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:BTN_VORD_1_FILTER_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:BTN_VORD_1_FILTER_ACTIVE] == 0	Set BTN_VORD_1_FILTER_ACTIVE (LVAR) to 1
[LVAR:BTN_VORD_1_FILTER_ACTIVE] == 1	Set BTN_VORD_1_FILTER_ACTIVE (LVAR) to 0

Row 1 Button 5	
Change Image	

[LVAR:BTN_WPT_1_FILTER_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:BTN_WPT_1_FILTER_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:BTN_WPT_1_FILTER_ACTIVE] == 0	Set BTN_WPT_1_FILTER_ACTIVE (LVAR) to 1
[LVAR:BTN_WPT_1_FILTER_ACTIVE] == 1	Set BTN_WPT_1_FILTER_ACTIVE (LVAR) to 0

Row 1 Button 6

Change Image

[LVAR:BTN_NDB_1_FILTER_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:BTN_NDB_1_FILTER_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:BTN_NDB_1_FILTER_ACTIVE] == 0	Set BTN_NDB_1_FILTER_ACTIVE (LVAR) to 1
[LVAR:BTN_NDB_1_FILTER_ACTIVE] == 1	Set BTN_NDB_1_FILTER_ACTIVE (LVAR) to 0

Row 1 Button 7

Change Image

[LVAR:BTN_ARPT_1_FILTER_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:BTN_ARPT_1_FILTER_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:BTN_ARPT_1_FILTER_ACTIVE] == 0	Set BTN_ARPT_1_FILTER_ACTIVE (LVAR) to 1
[LVAR:BTN_ARPT_1_FILTER_ACTIVE] == 1	Set BTN_ARPT_1_FILTER_ACTIVE (LVAR) to 0

Row 1 Button 8**Row 2 Button 1**

Button pressed for a short time (< 1 s)	Decrement KOHLSMAN SETTING MB by 1
---	------------------------------------

Row 2 Button 2**Row 2 Button 3**

Change Label

[MSFS:AUTOPILOT SPEED SLOT INDEX] == 1	Change [i]/i [b]_CONFIG[/b] to [b]!#('SPD'+ '\r\n\r\n'+[MSFS:AUTOPILOT AIRSPEED HOLD VAR:1])/[b]
--	--

[MSFS:AUTOPILOT SPEED SLOT INDEX] != 1	Change _CONFIG to SPD ---
--	---------------------------

Row 2 Button 4

Button pressed for a short time (< 1 s)	Send FCU SPD MACH TOGGLE PUSH-Event (Parameter: 0)
---	--

Row 2 Button 5

Change Label	
([LVAR:A32NX_FMA_LATERAL_MODE] == 0) && ([LVAR:A32NX_FMA_LATERAL_MODE] == 10) && ([LVAR:A32NX_FMA_LATERAL_MODE] == 1)	Change [i]/[i] [b]_CONFIG[/b] to [b]!#('HDG'+'\r\n\r\n'+[LVAR:A32NX_AUTOPILOT_HEADING_SELECTED])/[b]
([LVAR:A32NX_FMA_LATERAL_MODE] != 10) && ([LVAR:A32NX_FMA_LATERAL_MODE] != 11)	Change _CONFIG to HDG ---

Row 2 Button 6

Button pressed for a short time (< 1 s)	Send FCU TRK FPA TOGGLE PUSH-Event (Parameter: 0)
---	---

Row 2 Button 7

Change Label [MSFS:AUTOPILOT ALTITUDE LOCK VAR:3] != 0	Change [i]/[i] [b]_CONFIG[/b] to [b]!#('ALT'+'\r\n\r\n'+[MSFS:AUTOPILOT ALTITUDE LOCK VAR:3])/[b]
---	---

Row 2 Button 8

Button pressed for a short time (< 1 s)	
[LVAR:A32NX_METRIC_ALT_TOGGLE] == 0	Set A32NX_METRIC_ALT_TOGGLE (LVAR) to 1
[LVAR:A32NX_METRIC_ALT_TOGGLE] == 1	Set A32NX_METRIC_ALT_TOGGLE (LVAR) to 0

Row 3 Button 1

Change Image	
[SIMCONNECT:AUTOPILOT FLIGHT DIRECTOR ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[SIMCONNECT:AUTOPILOT FLIGHT DIRECTOR ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	Send TOGGLE_FLIGHT_DIRECTOR-Event (Parameter: 0)

Row 3 Button 2

Change Image	
--------------	--

A32NX FBW MSFS2020

[LVAR:BTN_LS_1_FILTER_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:BTN_LS_1_FILTER_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:BTN_LS_1_FILTER_ACTIVE] == 0	Set BTN_LS_1_FILTER_ACTIVE (LVAR) to 1
[LVAR:BTN_LS_1_FILTER_ACTIVE] == 1	Set BTN_LS_1_FILTER_ACTIVE (LVAR) to 0

Row 3 Button 3

Row 3 Button 4	
Change Image	
[LVAR:A32NX_AUTOPILOT_1_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:A32NX_AUTOPILOT_1_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	
Send FCU AP1 PUSH-Event (Parameter: 0)	

Row 3 Button 5	
Change Image	
[LVAR:A32NX_AUTOTHRUST_MODE] != 0	Change _CONFIG to FCU_ON(Profile)
[LVAR:A32NX_AUTOTHRUST_MODE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_AUTOTHRUST_MODE] == 0	Send AUTO_THROTTLE_ARM-Event (Parameter: 1)
[LVAR:A32NX_AUTOTHRUST_MODE] != 0	Set AUTOPILOT THROTTLE ARM to 0

Row 3 Button 6	
Change Image	
[LVAR:A32NX_AUTOPILOT_2_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:A32NX_AUTOPILOT_2_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	
Send FCU AP2 PUSH-Event (Parameter: 0)	

Row 3 Button 7	
Change Label	
[LVAR:A32NX_FMA_VERTICAL_MODE] == 14	Change [i][i] [b]_CONFIG[/b] to [b]!#('VS'+'\r\n\r\n'+[LVAR:A32NX_AUTOPILOT_VS_SELECTED])[/b]

[LVAR:A32NX_FMA_VERTICAL_MODE] == 15	Change [i]/[i] [b]_CONFIG[/b] to [b]!#('FPA'+'\r\n\r\n'+[LVAR:A32NX_AUTOPILOT_FPA_SELECTED]+'?')[/b]
([LVAR:A32NX_FMA_VERTICAL_MODE] != 14) && ([LVAR:A32NX_FMA_VERTICAL_MODE] != 15)	Change _CONFIG to VS/FPA ---

Row 3 Button 8

Row 4 Button 1

Row 4 Button 2

Change Label	
[LVAR:XMLVAR_NAV_AID_SWITCH_L1_STATE] == 0	Change _CONFIG to NAV AID 1 ---
[LVAR:XMLVAR_NAV_AID_SWITCH_L1_STATE] == 1	Change _CONFIG to NAV AID 1 ADF1
[LVAR:XMLVAR_NAV_AID_SWITCH_L1_STATE] == 2	Change _CONFIG to NAV AID 1 VOR1
Button pressed for a short time (< 1 s)	
[LVAR:XMLVAR_NAV_AID_SWITCH_L1_STATE] == 0	Set XMLVAR_NAV_AID_SWITCH_L1_STATE (LVAR) to 1
[LVAR:XMLVAR_NAV_AID_SWITCH_L1_STATE] == 1	Set XMLVAR_NAV_AID_SWITCH_L1_STATE (LVAR) to 2
[LVAR:XMLVAR_NAV_AID_SWITCH_L1_STATE] == 2	Set XMLVAR_NAV_AID_SWITCH_L1_STATE (LVAR) to 0

Row 4 Button 3

Change Label	
[LVAR:XMLVAR_NAV_AID_SWITCH_L2_STATE] == 0	Change _CONFIG to NAV AID 1 ---
[LVAR:XMLVAR_NAV_AID_SWITCH_L2_STATE] == 1	Change _CONFIG to NAV AID 1 ADF1
[LVAR:XMLVAR_NAV_AID_SWITCH_L2_STATE] == 2	Change _CONFIG to NAV AID 1 VOR1
Button pressed for a short time (< 1 s)	
[LVAR:XMLVAR_NAV_AID_SWITCH_L2_STATE] == 0	Set XMLVAR_NAV_AID_SWITCH_L2_STATE (LVAR) to 1
[LVAR:XMLVAR_NAV_AID_SWITCH_L2_STATE] == 1	Set XMLVAR_NAV_AID_SWITCH_L2_STATE (LVAR) to 2
[LVAR:XMLVAR_NAV_AID_SWITCH_L2_STATE] == 2	Set XMLVAR_NAV_AID_SWITCH_L2_STATE (LVAR) to 0

Row 4 Button 4

Change Image	
[LVAR:A32NX_FCU_LOC_MODE_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:A32NX_FCU_LOC_MODE_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)

Button pressed for a short time (< 1 s)	Send FCU LOC PUSH-Event (Parameter: 0)
---	--

Row 4 Button 5	
Change Image	
[LVAR:A32NX_FMA_EXPEDITE_MODE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:A32NX_FMA_EXPEDITE_MODE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	Send FCU EXPED PUSH-Event (Parameter: 0)

Row 4 Button 6	
Change Image	
[LVAR:A32NX_FCU_APPR_MODE_ACTIVE] == 1	Change _CONFIG to FCU_ON(Profile)
[LVAR:A32NX_FCU_APPR_MODE_ACTIVE] == 0	Change _CONFIG to FCU_OFF(Profile)
Button pressed for a short time (< 1 s)	Send FCU APPR PUSH-Event (Parameter: 0)

Row 4 Button 7	
-----------------------	--

Row 4 Button 8	
Button pressed for a short time (< 1 s)	Device: Switch to page/gauge MAIN

Page: Pedestal ({5ff1030f-bccb-4a19-b47d-28dacfce9782})

Row 1 Button 1	
Change Label [SIMCONNECT:ADF ACTIVE FREQUENCY:1] != 0	Change [i]/[i] [b]_CONFIG[/b] to [b]!#('ADF1'+'\r\n\r\n'+ [SIMCONNECT:ADF ACTIVE FREQUENCY:1])/[b]
Row 1 Button 2	
Change Label [SIMCONNECT:NAV ACTIVE FREQUENCY:1] != 0	Change [i]/[i] [b]_CONFIG[/b] to [b]!#('NAV1'+'\r\n\r\n'+ [SIMCONNECT:NAV ACTIVE FREQUENCY:1])/[b]
Row 1 Button 3	
Change Label [SIMCONNECT:NAV ACTIVE FREQUENCY:2] != 0	Change [i]/[i] [b]_CONFIG[/b] to [b]!#('NAV2'+'\r\n\r\n'+ [SIMCONNECT:NAV ACTIVE FREQUENCY:2])/[b]
Row 1 Button 4	
Change Label [SIMCONNECT:ADF ACTIVE FREQUENCY:2] != 0	Change [i]/[i] [b]_CONFIG[/b] to [b]!#('ADF2'+'\r\n\r\n'+ [SIMCONNECT:ADF ACTIVE FREQUENCY:2])/[b]
Row 1 Button 5	
Change Image [LVAR:A32NX_AUTOBRAKES_ARMED_MODE] == 1	Change _CONFIG to A320_Button_blue_on(Profile)
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] != 1	Change _CONFIG to A320_Button_blue_off(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] != 1	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 1 Send SET_AUTOBRAKE_CONTROL-Event (Parameter: 0)
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] == 1	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 0 Send SET_AUTOBRAKE_CONTROL-Event (Parameter: 1)
Row 1 Button 6	
Change Image [LVAR:A32NX_AUTOBRAKES_ARMED_MODE] == 2	Change _CONFIG to A320_Button_blue_on(Profile)
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] != 2	Change _CONFIG to A320_Button_blue_off(Profile)

A32NX FBW MSFS2020

Button pressed for a short time (< 1 s)	
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] != 2	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 2 Send SET_AUTOBRAKE_CONTROL-Event (Parameter: 0)
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] == 2	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 0 Send SET_AUTOBRAKE_CONTROL-Event (Parameter: 1)

Row 1 Button 7	
Change Image	
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] == 3	Change _CONFIG to A320_Button_blue_on(Profile)
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] != 3	Change _CONFIG to A320_Button_blue_off(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] != 3	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 3 Send SET_AUTOBRAKE_CONTROL-Event (Parameter: 0)
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] == 3	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 0 Send SET_AUTOBRAKE_CONTROL-Event (Parameter: 1)

Row 1 Button 8	
Change Image	
[LVAR:A32NX_BRAKE_FAN] == 1	Change _CONFIG to A320_Button_blue_on(Profile)
[LVAR:A32NX_BRAKE_FAN] == 0	Change _CONFIG to A320_Button_blue_off(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_BRAKE_FAN_BTN_PRESSED] == 0	Set A32NX_BRAKE_FAN_BTN_PRESSED (LVAR) to 1
[LVAR:A32NX_BRAKE_FAN_BTN_PRESSED] == 1	Set A32NX_BRAKE_FAN_BTN_PRESSED (LVAR) to 0

Row 2 Button 1	
Change Label [SIMCONNECT:COM ACTIVE FREQUENCY:1] != -1	Change [i]/i [b]_CONFIG[/b] to [b]!#[SIMCONNECT:COM ACTIVE FREQUENCY:1][/b]

Row 2 Button 2	
Button pressed for a short time (< 1 s)	Send COM1_RADIO_SWAP-Event (Parameter: 0)

Row 2 Button 3	
-----------------------	--

Change Label [SIMCONNECT:COM STANDBY FREQUENCY:1] != -1	Change [i]/i [b]_CONFIG[/b] to [b]!#[SIMCONNECT:COM STANDBY FREQUENCY:1][/b]
--	--

Row 2 Button 4

Row 2 Button 5	
Change Label	
[LVAR:A32NX_SPOILERS_ARMED] == 0	Change _CONFIG to SPD BRK ARM
[LVAR:A32NX_SPOILERS_ARMED] == 1	Change _CONFIG to SPD BRK ARMED
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_SPOILERS_ARMED] == 0	Send SPOILERS_SET-Event (Parameter: 0) Send SPOILERS_ARM_ON-Event (Parameter: 0)
[LVAR:A32NX_SPOILERS_ARMED] == 1	Send SPOILERS_ARM_OFF-Event (Parameter: 0)

Row 2 Button 6	
Change Image	
([SIMCONNECT:GEAR CENTER POSITION] == 0) && ([SIMCONNECT:GEAR LEFT POSITION] == 0) && ([SIMCONNECT:GEAR RIGHT POSITION] == 0) && ([SIMCONNECT:GEAR HANDLE POSITION] == 0)	Change _CONFIG to GearUpOk(Profile)
([SIMCONNECT:GEAR CENTER POSITION] != 0) && ([SIMCONNECT:GEAR LEFT POSITION] != 0) && ([SIMCONNECT:GEAR RIGHT POSITION] != 0) && ([SIMCONNECT:GEAR HANDLE POSITION] == 0)	Change _CONFIG to GearUpRed(Profile)
[SIMCONNECT:GEAR HANDLE POSITION] == 1	Change _CONFIG to GearUp(Profile)
Button pressed for a short time (< 1 s)	Send GEAR_UP-Event (Parameter: 0)

Row 2 Button 7

Row 2 Button 8

Row 3 Button 1

Change Label [SIMCONNECT:COM ACTIVE FREQUENCY:2] != -1	Change [i]/i [b]_CONFIG[/b] to [b]!#[SIMCONNECT:COM ACTIVE FREQUENCY:2][/b]
---	---

Row 3 Button 2	
Button pressed for a short time (< 1 s)	Send COM2_RADIO_SWAP-Event (Parameter: 0)

Row 3 Button 3	
Change Label [SIMCONNECT:COM STANDBY FREQUENCY:2] != -1	Change [i]/i [b]_CONFIG[/b] to [b]!#[SIMCONNECT:COM STANDBY FREQUENCY:3][/b]

Row 3 Button 4	
-----------------------	--

Row 3 Button 5	
Change Image	
[LVAR:A32NX_SPOILERS_HANDLE_POSITION] == 0	Change _CONFIG to GearUpOk(Profile)
[LVAR:A32NX_SPOILERS_HANDLE_POSITION] > 0	Change _CONFIG to GearUp(Profile)
Button pressed for a short time (< 1 s)	Send SPOILERS_SET-Event (Parameter: 0)

Row 3 Button 6	
Change Image	
([SIMCONNECT:GEAR CENTER POSITION] == 100) && ([SIMCONNECT:GEAR LEFT POSITION] == 100) && ([SIMCONNECT:GEAR RIGHT POSITION] == 100)	Change _CONFIG to GearDownOk(Profile)
([SIMCONNECT:GEAR CENTER POSITION] != 100) && ([SIMCONNECT:GEAR LEFT POSITION] != 100) && ([SIMCONNECT:GEAR RIGHT POSITION] != 100) && ([SIMCONNECT:GEAR HANDLE POSITION] == 0)	Change _CONFIG to GearDown(Profile)
([SIMCONNECT:GEAR CENTER POSITION] != 100) && ([SIMCONNECT:GEAR LEFT POSITION] != 100) && ([SIMCONNECT:GEAR RIGHT POSITION] != 100) && ([SIMCONNECT:GEAR HANDLE POSITION] == 1)	Change _CONFIG to GearDownRed(Profile)
Button pressed for a short time (< 1 s)	Send GEAR_DOWN-Event (Parameter: 0)

Row 3 Button 7	
Change Image	
[LVAR:A32NX_FLAPS_HANDLE_INDEX] == 0	Change _CONFIG to GearUpOk(Profile)
[LVAR:A32NX_FLAPS_HANDLE_INDEX] != 0	Change _CONFIG to GearUp(Profile)
Button pressed for a short time (< 1 s)	Send FLAPS_DECR-Event (Parameter: 0)

Row 3 Button 8

Row 4 Button 1

Row 4 Button 2	
Change Label	
[SIMCONNECT:TRANSPONDER CODE:1] != -1	Change [i]/i [b]_CONFIG[/b] to [b]!#('Squawk'+'\r\n\r\n'+[SIMCONNECT:TRANSPONDER CODE:1])/b]

Row 4 Button 3	
Change Label	
[MSFS:TRANSPONDER STATE:1] != 4	Change _CONFIG to ATC STBY
[MSFS:TRANSPONDER STATE:1] == 4	Change _CONFIG to ATC ON
Button pressed for a short time (< 1 s)	
[MSFS:TRANSPONDER STATE:1] != 4	Set TRANSPONDER STATE:1 to 4
[MSFS:TRANSPONDER STATE:1] == 4	Set TRANSPONDER STATE:1 to 1

Row 4 Button 4

Row 4 Button 5	
Change Image	
[LVAR:A32NX_SPOILERS_HANDLE_POSITION] > 0	Change _CONFIG to GearDownOk(Profile)
[LVAR:A32NX_SPOILERS_HANDLE_POSITION] == 0	Change _CONFIG to GearDown(Profile)
Change Label	
[LVAR:A32NX_SPOILERS_HANDLE_POSITION] != -1	Change [i]/i [b]_CONFIG[/b] to [b]!#(ROUND([LVAR:A32NX_SPOILERS_HANDLE_POSITION],2))/b]
Button pressed for a short time (< 1 s)	Send SPOILERS_SET-Event (Parameter: 16384)

Row 4 Button 6

A32NX FBW MSFS2020

Change Image	
[LVAR:A32NX_PARK_BRAKE_LEVER_POS] == 1	Change _CONFIG to PBreak_ON(Profile)
[LVAR:A32NX_PARK_BRAKE_LEVER_POS] == 0	Change _CONFIG to PBreak_OFF(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_PARK_BRAKE_LEVER_POS] == 1	Send PARKING_BRAKES-Event (Parameter: 0)
[LVAR:A32NX_PARK_BRAKE_LEVER_POS] == 0	Send PARKING_BRAKES-Event (Parameter: 1)

Row 4 Button 7	
Change Image	
[LVAR:A32NX_FLAPS_HANDLE_INDEX] == 4	Change _CONFIG to GearDownOk(Profile)
[LVAR:A32NX_FLAPS_HANDLE_INDEX] != 4	Change _CONFIG to GearDown(Profile)
Change Label [LVAR:A32NX_FLAPS_HANDLE_INDEX] != -1	Change [i]/i [b]_CONFIG[/b] to [b]!#[(LVAR:A32NX_FLAPS_HANDLE_INDEX)][/b]
Button pressed for a short time (< 1 s)	Send FLAPS_INCR-Event (Parameter: 0)

Row 4 Button 8	
Button pressed for a short time (< 1 s)	Device: Switch to page/gauge MAIN

Page: Test Page ({75244b18-a265-48e8-8001-2cfbba13926c})

Row 1 Button 1	
Button pressed for a short time (< 1 s)	Send FCU AP DISCONNECT-Event (Parameter: 0)
Row 1 Button 2	
Button pressed for a short time (< 1 s)	Send FCU ATHR PUSH-Event (Parameter: 0)
Row 1 Button 3	
Button pressed for a short time (< 1 s)	Send FCU ATHR DISCONNECT-Event (Parameter: 0)
Row 1 Button 4	
Button pressed for a short time (< 1 s)	Send FCU HDG INC-Event (Parameter: 0)
Row 1 Button 5	
Button pressed for a short time (< 1 s)	Send FCU HDG DEC-Event (Parameter: 0)
Row 1 Button 6	
Button pressed for a short time (< 1 s)	Send FCU HDG SET-Event (Parameter: 299)
Row 1 Button 7	
Button pressed for a short time (< 1 s)	Send FCU ALT INC-Event (Parameter: 0)
Row 1 Button 8	
Button pressed for a short time (< 1 s)	Send FCU ALT DEC-Event (Parameter: 0)
Row 2 Button 1	
Button pressed for a short time (< 1 s)	Send FCU ALT SET-Event (Parameter: 18000)
Row 2 Button 2	
Button pressed for a short time (< 1 s)	Send FCU VS INC-Event (Parameter: 0)

A32NX FBW MSFS2020

Row 2 Button 3	
Button pressed for a short time (< 1 s)	Send FCU VS DEC-Event (Parameter: 0)
Row 2 Button 4	
Button pressed for a short time (< 1 s)	Send FCU VS SET-Event (Parameter: 30)
Row 2 Button 5	
Change Image	
[LVAR:A32NX_AIRCOND_PACK1_TOGGLE] == 0	Change _CONFIG to A320_Button_white_off(Profile)
[LVAR:A32NX_AIRCOND_PACK1_TOGGLE] == 1	Change _CONFIG to A320_Button_white_on(Profile)
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_AIRCOND_PACK1_TOGGLE] == 1	Set A32NX_AIRCOND_PACK1_TOGGLE (LVAR) to 0
[LVAR:A32NX_AIRCOND_PACK1_TOGGLE] == 0	Set A32NX_AIRCOND_PACK1_TOGGLE (LVAR) to 1
Row 2 Button 6	
Row 2 Button 7	
Button pressed for a short time (< 1 s)	Send FCU ALT INC-Event (Parameter: 100)
Row 2 Button 8	
Button pressed for a short time (< 1 s)	Send FCU ALT DEC-Event (Parameter: 0)
Row 3 Button 1	
Button pressed for a short time (< 1 s)	Set A32NX_OVHD_INTLT_ANN (LVAR) to 1
Row 3 Button 2	
Button pressed for a short time (< 1 s)	Set A32NX_OVHD_INTLT_ANN (LVAR) to 2
Row 3 Button 3	
Button pressed for a short time (< 1 s)	
[LVAR:A32NX_AVIONICS_COMPLT_ON] == 0	Set A32NX_AVIONICS_COMPLT_ON (LVAR) to 1
[LVAR:A32NX_AVIONICS_COMPLT_ON] == 1	Set A32NX_AVIONICS_COMPLT_ON (LVAR) to 0

Row 3 Button 4	
Scripted event	
([LOCAL:TEMP1] == 0) && ([LOCAL:TEMP1] == 1)	Change _CONFIG to AIRBUS PANEL(Profile) Delay execution for 1000 ms. Set TEMP1 (Session) to 1
[LOCAL:TEMP1] == 1	Change _CONFIG to OFF Delay execution for 1000 ms. Set TEMP1 (Session) to 0
Row 3 Button 5	
Row 3 Button 6	
Row 3 Button 7	
Button pressed for a short time (< 1 s)	Send FCU ALT INC-Event (Parameter: 1000)
Row 3 Button 8	
Button pressed for a short time (< 1 s)	Send FCU ALT DEC-Event (Parameter: 1000)
Row 4 Button 1	
Row 4 Button 2	
Row 4 Button 3	
Row 4 Button 4	
Change Image	
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] == 3	Change _CONFIG to A320_Button_blue_on(Profile)
[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] != 3	Change _CONFIG to A320_Button_blue_off(Profile)
Button pressed for a short time (< 1 s)	
([LVAR:A32NX_AUTOBRAKES_ARMED_MODE] != 3) && ([SIMCONNECT:SIM ON GROUND] == 1)	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 3 Send SET_AUTOBRAKE_CONTROL-Event (Parameter: 0)

[LVAR:A32NX_AUTOBRAKES_ARMED_MODE] == 3	Set A32NX_AUTOBRAKES_ARMED_MODE (LVAR) to 0 Send SET_AUTOBRAKE_CONTROL-Event (Parameter: 1)
---	--

Row 4 Button 5

Row 4 Button 6

Row 4 Button 7

Button pressed for a short time (< 1 s)	Send FCU ALT INC-Event (Parameter: 750)
---	---

Row 4 Button 8

Button pressed for a short time (< 1 s)	Device: Switch to page/gauge MAIN
---	-----------------------------------

T.16000M (T.16000M)

SLIDER	
Axis change	
	Left toe brake
	Right toe brake